

# TECHNICAL SHEET

15-440

# G-TEK® SUPRENE™ BLENDED GLOVE WITH NEOFOAM™ COATED GRIP

- Suprene<sup>™</sup> fiber shell is 100 times stronger than steel and is amongst the highest performing fibers in cut and tear resistance
- Seamless knit construction provides comfort without sacrificing dexterity
- Neofoam™ coated palm and fingertips offers great abrasion resistance and outstanding wet/dry grip
- Touch screen compatible to allow the user to operate a touchscreen phone or device without removing gloves
- Knit Wrist helps prevent dirt and debris from entering the glove
- Cotton color binding denotes sizing
- Launderable for extended life and to reduce replacement costs
- Silicone free

# **APPLICATIONS**

- Electronics
- · General duty
- · Parts assembly
- Construction

#### **CARE INSTRUCTIONS**

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low - maximum temperature 140°F (60°C).

## **TECHNICAL DATA**

| MATERIAL        | Suprene™ Engineered Yarn / NeoFoam™ Coating           |          |         |          |         |          |  |
|-----------------|---|----------|---------|----------|---------|----------|--|
| CONSTRUCTION    | Seamless knit   |          |         |          |         |          |  |
| COLOR           | Shell: ■ Tan/ Coating: ■ Black                        |          |         |          |         |          |  |
| WRIST STYLE     | Knitted   |          |         |          |         |          |  |
| SIZES           | 6 -11   |          |         |          |         |          |  |
| PACKAGING       | 1 pair per bag, 12 pairs per dozen, 72 pairs per case |          |         |          |         |          |  |
| CASE DIMENSIONS | 15" x 11.8" x 10.6" / 38cm x 30cm x 27cm              |          |         |          |         |          |  |
| CASE WEIGHT     | 6   | 7        | 8       | 9        | 10      | 11       |  |
|                 | 7.5 lbs   | 8 lbs    | 8.8 lbs | 10.4 lbs | 11 lbs  | 11.3 lbs |  |
|                 | 3.4 kgs   | 3.7 kgss | 4 kgs   | 4.7 kgs  | 4.9 kgs | 5.2 kgs  |  |
| C00             | China   |          |         |          |         |          |  |

#### **PERFORMANCE PROPERTIES**

| EN388: 4542 | ASTM F2992-15 ANSI Cut Level A4 (Adopted by ANSI/ISEA 02/16) |   |   |   |   |   |
|-------------|--|---|---|---|---|---|
| ABRASION    | 0  | 1 | 2 | 3 | 4 | - |
| CUT (2003)  | 0  | 1 | 2 | 3 | 4 | 5 |
| TEAR        | 0  | 1 | 2 | 3 | 4 | - |
| PUNCTURE    | 0  | 1 | 2 | 3 | 4 | - |







### **DIMENSIONS (IN/CM)**

|   |           |           |           |           |           | 11         |
|---|-----------|-----------|-----------|-----------|-----------|------------|
|   | 8.6 / 22  | 9 / 23    | 9.4 / 24  | 9.8 / 25  | 10.2 / 26 | 10.6 / 27  |
|   | 2.8 / 7.2 | 3.2 / 8.2 | 3.6 / 9.2 | 3.8 / 9.7 | 3.9 / 10  | 4.1 / 10.3 |
| Н | Purple    | Red       | Yellow    | Brown     | ■ Black   | Blue       |

