



TECHNICAL SHEET

16-560E



G-TEK® POLYKOR™ SEAMLESS KNIT BLENDED GLOVE WITH POLYURETHANE COATED SMOOTH GRIP

- Seamless construction offers increased comfort and breathability
- PolyKor™ shell is lightweight and provides excellent dexterity, tactile sensitivity and cut resistance
- Polyurethane coated palm and fingertips for great abrasion resistance, excellent puncture resistance and outstanding wet/dry grip
- Knit wrist helps prevent dirt and debris from entering the glove
- Economy and performance
- Cotton color binding denotes sizing
- Washable, resistant to chemicals, water, and ultraviolet light

APPLICATIONS

- Electronics
- Glass cutting
- Sheet metal handling
- General duty
- Parts assembly
- Sharp small parts handling

CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low - maximum temperature 140°F (60°C).




TECHNICAL DATA

MATERIAL	PolyKor™ Fiber / Polyurethane					
CONSTRUCTION	Seamless knit					
COLOR	Shell: ■ Gray / Coating: ■ Gray					
WRIST STYLE	Knit wrist					
SIZES	6 -11					
PACKAGING	1 pair per bag, 12 pairs per dozen, 72 pairs per case					
CASE DIMENSIONS	14.2" x 11.8" x 12.6" / 36cm x 30cm x 32cm					
CASE WEIGHT	6	7	8	9	10	11
	8.4 lbs 3.8 kgs	8.8 lbs 4 kgss	9.7 lbs 4.4 kgs	10.1 lbs 4.6 kgs	10.6 lbs 4.8 kgs	11.9 lbs 5.4 kgs
COO	China					

DIMENSIONS (IN/CM)

	6	7	8	9	10	11
A	8.6 / 22	8.9 / 22.5	9.3 / 23.5	9.6 / 24.5	10 / 25.5	10.6 / 27
B	3.5 / 9	3.7 / 9.5	3.8 / 9.8	3.9 / 10	4.1 / 10.5	4.3 / 11
C	■ Purple	■ Red	■ Yellow	■ Brown	■ Black	■ Blue



PERFORMANCE PROPERTIES

EN388: 4543	ASTM F2992-15 ANSI Cut Level A4 (Adopted by ANSI/ISEA 02/16)					
ABRASION	0	1	2	3	4	-
CUT (2003)	0	1	2	3	4	5
TEAR	0	1	2	3	4	-
PUNCTURE	0	1	2	3	4	-

PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

PIP FRANCE SAS | 120 Grande Rue | 85570 L'Hermenault | Tel: +33 2 51 50 19 80 | info@pipeurope.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED.