



# TECHNICAL SHEET

## 16-820



### G-TEK® CR SEAMLESS KNIT POLYKOR™ BLENDED GLOVE WITH ACRYLIC LINING AND DOUBLE-DIPPED LATEX COATED MICRO-SURFACE GRIP

- Seamless construction offers increased comfort and breathability
- PolyKor™ shell is lightweight and provides excellent dexterity, tactile sensitivity and cut resistance
- Double-dipped latex "Micro-Surface" coated palm and knuckles help extend the life of the glove and provide excellent abrasion resistance
- Knit wrist helps prevent dirt and debris from entering the glove
- Washable, resistant to chemicals, water, and ultraviolet light

#### APPLICATIONS

- Electronics
- Glass cutting
- Sheet metal handling
- Parts assembly
- Sharp small parts handling
- Construction
- General duty applications

#### CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low - maximum temperature 140°F (60°C).



#### TECHNICAL DATA

MATERIAL	13 gauge PolyKor™ outer shell/acrylic inner shell with latex				
CONSTRUCTION	Seamless knit				
COLOR	Shell: ■ Salt&Pepper / Coating: ■ Black/Blue				
WRIST STYLE	Knitted				
SIZES	7 -11				
PACKAGING	12 pairs per dozen, 72 pairs per case				
CASE DIMENSIONS	31.5" x 11.8" x 10.2" / 80cm x 30cm x 26cm				
CASE WEIGHT	7	8	9	10	11
	20.5 lbs 9.3 kgs	21 lbs 9.5 kgs	22.3 lbs 10.1 kgs	24 lbs 10.9 kgs	24.3 lbs 11 kgs
COO	China				

#### PERFORMANCE PROPERTIES

EN388: 3543	ASTM F2992-15 ANSI Cut Level A3 (Adopted by ANSI/ISEA 02/16)					
ABRASION	0	1	2	3	4	-
CUT (2003)	0	1	2	3	4	5
TEAR	0	1	2	3	4	-
PUNCTURE	0	1	2	3	4	-

#### DIMENSIONS (IN/CM)

	7	8	9	10	11
A	9.8 / 25	10.2 / 26	10.4 / 26.5	10.8 / 27.5	11 / 28
B	4.1 / 10.3	4.2 / 10.7	4.3 / 11	4.5 / 11.3	4.6 / 11.7
C	■ Red	■ Yellow	■ Brown	■ Black	■ Blue

