

TECHNICAL SHEET

16-323FT

G-TEK® POLYKOR® HI-VIS SEAMLESS KNIT POLYKOR® BLENDED GLOVE WITH NITRILE COATED FOAM GRIP - 15 GAUGE

- PolyKor® blended shell is lightweight and provides excellent dexterity, tactile sensitivity and cut resistance
- · Seamless construction offers increased comfort and breathability
- Foam nitrile coated palm and fingers are compatible with light oils and will provide a good grip and excellent abrasion resistance
- · Reinforced thumb crotch for longer wear
- 2 fingers & thumb middle finger and index finger are cut at the level of the first phalanx in order to maintain total sensitivity on f ingertips while protecting the rest of the hand. Cut resistant level B
- Knit wrist helps prevent dirt and debris from entering the glove
- Hi-Vis coloring makes this product very easy to see
- · Cotton color binding denotes sizing
- Washable, resistant to chemicals, water, and ultraviolet light

APPLICATIONS

- Aeronautics
- · Assembly of metal parts and components
- · Finishing work,
- · Cutting small dry or lightly oiled parts
- · Plastic injection and molding

CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low - maximum temperature 140°F (60°C).

TECHNICAL DATA

MATERIAL	PolyKor® Engineered Yarn / Nitrile Coating					
CONSTRUCTION	Seamless knit					
COLOR	Shell: Hi-Vis lime yellow / Coating: ■ Gray					
WRIST STYLE	Knit wrist					
SIZES	8 -11					
PACKAGING	1 pair per bag, 12 pairs per dozen, 72 pairs per case					
CASE DIMENSIONS	14.2" x 11.8" x 12.6" / 36cm x 30cm x 32cm					
CASE WEIGHT			8	9	10	11
			8.4 lbs	9.3 lbs	9.9 lbs	11 lbs
			3.8 kgs	4.2 kgs	4.5 kgs	5 kgs
C00	China					

PERFORMANCE PROPERTIES

EN388: 4X31B	ASTM F2992-15 ANSI Cut Level A2 (Adopted by ANSI/ISEA 02/16)					
ABRASION	0	1	2	3	4	-
CUT (2003)	Х	1	2	3	4	5
TEAR	0	1	2	3	4	-
PUNCTURE	0	1	2	3	4	-
CUT (13997)	А	В	С	D	Е	F







DIMENSIONS (IN/CM)

				11
A	9 / 23	9.6 / 24.5	10.2 / 26	10.6 / 27
В	3.7 / 9.5	3.9 / 10	4.1 / 10.5	4.3 / 11
Н	Yellow	■ Brown	■ Black	Blue

