



TECHNICAL SHEET

16-E160

G-TEK® 15G POLYKOR™ GLOVE WITH POLYURETHANE COATING



- Seamless construction offers increased comfort and breathability
- PolyKor™ blended shell is lightweight and provides excellent dexterity, tactile sensitivity and cut resistance
- Polyurethane coated palm and fingertips for great abrasion resistance, tear resistance and outstanding dry grip
- Gauge 15
- Knit Wrist helps prevent dirt and debris from entering the glove
- Washable for extended life and reduced replacement costs

APPLICATIONS

- Parts assembly and inspection
- Equipment assembly and disassembly
- Loading and unloading of trucks and vehicles
- Goods handling
- Maintenance/Upkeep
- Draining of pumps, valves or pipes
- Locksmith

CARE INSTRUCTIONS

It is recommended to clean the gloves in temperate water with a maximum temperature of 40°C once. A mild non-ionic detergent should be used. A drying time of 5-10 minutes should be used.

Tumble dry low - max temperature 30°C.

TECHNICAL DATA

MATERIAL	PolyKor™ Fiber / Polyurethane
CONSTRUCTION	Seamless knit
COLOR	Shell: <input type="checkbox"/> White / Coating: <input checked="" type="checkbox"/> Gray
WRIST STYLE	Continuous knit
SIZES	6 -11
PACKAGING	12 pairs per biodegradable polybag, 72 pairs per case
COO	China

PERFORMANCE PROPERTIES

EN388: 4X42B	ASTM F2992-15 ANSI Cut Level A2 (Adopted by ANSI/ISEA 02/16)					
ABRASION	0	1	2	3	4	-
CUT (2003)	X	1	2	3	4	5
TEAR	0	1	2	3	4	-
PUNCTURE	0	1	2	3	4	-
CUT (ISO 13997)	A	B	C	D	E	F



DIMENSIONS (IN/CM)

	6	7	8	9	10	11
A	8.2 / 21	8.6 / 22	8.9 / 22.5	9.4 / 24	9.8 / 25	10.2 / 26
B	3.3 / 8.5	3.5 / 9	3.7 / 9.5	3.9 / 10	4.1 / 10.5	4.3 / 11
H	<input checked="" type="checkbox"/> Purple	<input checked="" type="checkbox"/> Red	<input checked="" type="checkbox"/> Yellow	<input checked="" type="checkbox"/> Brown	<input checked="" type="checkbox"/> Black	<input checked="" type="checkbox"/> Blue

